



### SPECIAL FEATURES

- ❖ High Efficiency, 80 PLUS® Gold Certified
- ❖ Fully Modular
- ❖ Top-Quality 135 mm Fluid Dynamic Bearing Fan
- ❖ Hybrid Five-Way Fan Control
- ❖ Micro Tolerance Load Regulation (MTLR) [0.5 %]
- ❖ Super Low Ripple Noise [under 20 mV]
- ❖ Cable-free Connection Design
- ❖ Gold Plated High Current Terminal (MB, CPU and PCIe)
- ❖ Multi-GPU Technology Support

### POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
<b>PRIME</b> AirTouch 850 Gold	20 A	20 A	70 A	0.3 A	2.5 A	850 W
	100 W		840 W	3.6 W	12.5 W	



### WIRE CONFIGURATION

Cable						
Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	FDD (4P)
<b>PRIME</b> AirTouch 850 Gold	1	2	6	10	5	1



Safety & EMI / EMC

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 170 mm (L) x 150 mm (W) x 86 mm (H)



Specifications may change without prior notice



**Headquarters** sales@seasonic.com  
**USA** ssa.sales@seasonic.com  
**Europe** sse.sales@seasonic.com