1000 W / 850 W / 750 W

FOCUS GX ATX 3.1



SPECIAL FEATURES

- ATX 3.1 and PCIe 5.1
- High Efficiency and Quiet, Cybenetics ETA Platinum and Lambda A
- OptiSink™ Thermal Design
- OptiSilent Fan Control
- 135 mm Fluid Dynamic Bearing (FDB) Fan
- Fully Modular Cabling Design with Patented Cable Combs
- Native Dual-Color 12V-2x6 Cable
- Highly Reliable Japanese 105 ºC Aluminum Electrolytic Capacitors
- Tight Voltage Regulation (12 V, 5 V, 3.3 V)
- Cable-free Connection Design
- Compact size (140 mm)
- Multi-GPU Technology Support



POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
FOCUS GX-1000	25 A	25 A	83 A	0.3 A	3 A	1000 W
	125 W		996 W	3.6 W	15 W	
FOCUS GX-850	20 A	20 A	70 A	0.3 A	3 A	850 W
	100 W		840 W	3.6 W	15 W	
FOCUS GX-750	20 A	20 A	62 A	0.3 A	3 A	750 W
	100 W		744 W	3.6 W	15 W	

CONNECTOR QUANTITY

Model \ Cable	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (4P) 750 mm	12V-2x6 700 mm	12V-2x6 to 2 x 8P 700 mm	PCI-E (8P / 6P) 750 mm	SATA 500 mm	3Molex 450 mm
FOCUS GX-1000	1	2	1	1	2	2	1
FOCUS GX-850	1	2	1	1	2	2	1
FOCUS GX-750	1	2	1	1	1	2	1



Compliance: CB R33080

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 140 mm (L) x 150 mm (W) x 86 mm (H)

Specifications may change without prior notice

Headquarters sales@seasonic.com
USA ssa.sales@seasonic.com
Europe sse.sales@seasonic.com

www.seasonic.com